

Qty. Description

1 UPS 50-185 F



Note! Product picture may differ from actual product

Product No.: [96430300](#)

The pump is of the canned rotor type, i.e. pump and motor form an integral unit without shaft seal and with only two gaskets for sealing. The bearings are lubricated by the pumped liquid.

In order to avoid problems in connection with disposal, great importance has been attached to using as few different materials as possible.

The pump is characterized by:

- Speed no: * 3 speed motor.
- * Ceramic radial bearings.
- * Carbon axial bearing.
- * Stainless steel rotor can, bearing plate and rotor cladding.
- * Aluminium alloy stator housing.
- Pump housing: * Cast iron pump housing.
- * Stator with built-in thermal switch.

Phase: The motor is a 1-phase motor.

The pump is supplied with a standard module in the terminal box. The standard module is to be connected to the mains supply via external contactor.

Controls:
 Relay: without relay

Liquid:
 Pumped liquid: Water
 Liquid temperature range: -10 .. 120 °C
 Selected liquid temperature: 60 °C
 Density: 983.2 kg/m³

Technical:
 Approvals on nameplate: AAA,EAC

Materials:
 Pump housing: Cast iron
 EN-JL1040
 ASTM 35 B - 40 B
 Impeller: Stainless steel
 DIN W.-Nr. 1.4301
 AISI 304

Installation:
 Range of ambient temperature: 0 .. 40 °C

Qty.	Description
	<p>Maximum operating pressure: 10 bar Flange standard: DIN Pipe connection: DN 50 Pressure rating: PN 6 / PN 10 Port-to-port length: 280 mm</p> <p>Electrical data: Power input in speed 1: 1150 W Power input in speed 2: 1240 W Max. power input: 1290 W Mains frequency: 50 Hz Rated voltage: 1 x 230-240 V Current in speed 1: 5.6 A Current in speed 2: 6.05 A Current in speed 3: 6 A Cos phi in speed 1: 0.89 Cos phi in speed 2: 0.89 Cos phi: 0.93 Capacitor size - run: 30 μF/400 V Insulation class (IEC 85): H Enclosure class (IEC 60529): X4D</p> <p>Others: Net weight: 28 kg Gross weight: 29.1 kg Shipping volume: 0.043 m³</p>