

## DEVireg™ 850 IV



The DEVireg™ 850 version IV is an advanced thermostat with LED display used for outdoor ground or roof applications. The sensors provide information about both moisture level and temperature, resulting in an optimal control of the heating system.

The DEVireg™ 850 IV can handle up to 2 independent areas, in any of the following combinations:

- Single system for roof or ground (1 system, 1–4 sensors).
- Combination system: 1 ground system and 1 roof system (2 systems, 2–4 sensors total, min. 1 sensor per system).
- Dual system: either 2 roof systems or 2 ground systems (2 systems, 2–4 sensors total, min. 1 sensor per system).

In the dual / combination systems it is possible to prioritize between the zones, e.g. if only a limited power output is available.

Benefits:	Type	Value	
<ul style="list-style-type: none"> <li>• Single, combination or dual zones</li> <li>• Up to 4 sensors</li> <li>• Moisture and temperature sensing</li> <li>• Self diagnosing programme</li> <li>• Safety level adjustment</li> <li>• Alarm function</li> </ul>	Operation voltage: PSU 24 VDC DEVireg™ 850 IV	180–250 VAC, 50–60 Hz / 24 VDC 24 VDC ±10%	
	Power consumption, max.: DEVireg™ 850 IV Roof sensor Ground sensor	3 W 8 W (each) 13 W (each)	
	Relay resistive load, max.: System A / B relay Alarm relay Inductive load each relay, max.	15 A (3450 W) @ 230 V 2 A @ 230 V 1 A @ 230 V, power factor 0,3	
	Sensing unit	DEVibus™ connected moisture sensor(s)	
	Cable specification for terminals max.	1 x 4 mm <sup>2</sup> or 2 x 2,5 mm <sup>2</sup>	
	Ball pressure test temperature	75 °C	
	Pollution degree	2 (domestic use)	
	Controller type	1 C	
	Storage temperature	-20 °C to +65 °C	
	IP class	IP 20	
Standard compliance:	Protection class	Class II - <input type="checkbox"/>	
<ul style="list-style-type: none"> <li>• EN/IEC 60730-1 (general)</li> <li>• EN/IEC 60730-2-9 (thermostat)</li> </ul>	Dimensions (H/W/D): PSU 24 VDC DEVireg™ 850 IV	85 x 73 x 53 mm 85 x 105 x 53 mm	
	Mounting method	DIN rail	
	Weight	720 g	
	Versions (languages)	Latin: GB, CZ, DE, DK, ES, EST, FI, FR, HR, HU, LT, LV, NL, NO, PL, SCG, SE, SI, SK, TR. Cyrillic: GB, BG, RO, RU.	
	Approvals:		

### Types

Item no.	Product name	Type	Size, mm	Ambient temperature	EAN no.
140F1084	<b>DEVireg™ 850 IV Cyrillic with PSU</b>	Without sensors, Cyrillic languages	85 x 105 x 53	-10...+50 °C	5703466210833
140F1085	<b>DEVireg™ 850 IV Latin with PSU</b>	Without sensors, Latin languages	85 x 105 x 53	-10...+50 °C	5703466209264

### Accessories

Item no.	Product name	Type	Size, mm	Ambient temperature	EAN no.
140F1086	<b>Roof sensor for DEVireg™ 850</b>	For DEVireg™ 850, with sensor tube, cable - 15 m	15 x 24 x 216	-50...+70 °C	5703466209271
140F1087	<b>Ground sensor for DEVireg™ 850, 2 pcs.</b>	For DEVireg™ 850, with sensor tube, cable - 15 m	∅ 93 x 98	-30...+70 °C	5703466209288
140F1088	<b>Ground sensor for DEVireg™ 850, 1 pc.</b>	For DEVireg™ 850, cable - 15 m	∅ 93 x 98	-30...+70 °C	5703466209714
140F1089	<b>Power Supply Unit</b>	PSU CP-D 24/2.5 100-240VAC/24VDC DINrail	85 x 73 x 53	-10...+40 °C	5703466209721
19119977	<b>Sensor tube and cup</b>	For Outdoor Sensor DEVireg™ 850	∅ 93 x 98	-30...+70 °C	5703466208359



DEVIreg™ 850 IV with PSU



Roof sensor




Ground sensor



Sensor tube and cup for Ground sensor


**Connection scheme DEVIreg™ 850 IV**




**System configurations**

Zone support saves energy


DEVIreg™ 850 lets you divide your area in to 2 zones, e.g. a North and South side. In this way it is possible to save energy, when the South side is free of ice and snow faster because of the heat from the sun.




Single zone system for roofs  
(system A)




Single zone system for ground  
(system A)



Combined system -  
one zone for roof (system A),  
one zone for ground (system B)



Two zone system for roofs  
(systems A and B)



Two zone system for ground  
(systems A and B)